

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. ONCO-002

First Inventor or Application Identifier Richard C. Fenwick, Jr.

Title Allocating Computer Resources Within...

Express Mail Label No. EL048467211US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 34]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 2]
4. Oath or Declaration [Total Pages]
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a
copy of the oath or declaration is supplied under Box 4b, is
considered to be part of the disclosure of the accompanying
application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS/PTO-1449 Citations)
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
 - * Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
(PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other: ..Transmittal Letter.....

* NOTE FOR ITEMS 1 & 14: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY
FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT
IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____ Group / Art Unit: _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name	Stephen R. Uriarte				
	D'Alessandro & Ritchie				
Address	P.O. Box 640640				
City	San Jose	State	CA	Zip Code	95164-0640
Country	USA	Telephone	408-441-1100	Fax	408-441-8400

Name (Print/Type)	Stephen R. Uriarte	Registration No. (Attorney/Agent)	40,854
Signature		Date	12/31/98

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

This application is submitted in the name of inventors Richard C. Fenwick, Jr., Donald W. Power, Brian G. Barnett and John T. Miner, all assignors to On Command Corporation, a Delaware Corporation.

5

SPECIFICATION

TITLE OF INVENTION

ALLOCATING COMPUTER RESOURCES WITHIN A VIDEO

10

DISTRIBUTION SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

15

The present invention relates to systems for video distribution. More particularly, the present invention relates to a video distribution system utilizing a host computing device that allocates tasks among a number of audiovisual serving devices.

20

The Background

It is common for lodging facilities such as hotels and motels to provide their guests with video programming from cable or broadcast television as well as feature films via on-demand video rentals and/or fixed scheduled movie systems.

Providing video programming beyond the cable and broadcast television programming readily available to the public allows the facility to both fulfill a desire of some guests for such programming and generate revenue by charging for the programming.

5 Recently it has become almost mandatory for travellers to maintain electronic communication with their employees' computers and with e-mail servers in general so that they receive e-mail while on the road. Typically this has been achieved by requiring the traveller to carry a portable computer, modem, server supply and related materials on the road in order to effectuate such
10 communications. Thus, in the past, travellers have been required to either carry a computer with them or find a facility with a computer that can be borrowed.

 Prior art systems for video distribution function with fixed and defined video hardware. There is no known prior art system based on a design where a host computing device allocates numerous tasks to audiovisual serving devices
15 such as assignable computing devices. No known prior art systems provides for internet access over a conventional video distribution systems with out the need for a computing device at the terminus of the video distribution systems, e.g., the user's room

 Accordingly, it would be desirable to provide an improved video
20 distribution system based on a host computing device and a number of audiovisual serving devices for distributing program material from a plurality of sources including the internet to users.

SUMMARY OF THE INVENTION

A method and system for video distribution among a plurality of users uses

5 a host computing device that allocates tasks among a number of audiovisual serving devices. The system architecture permits a single host to handle a plurality of simultaneous users and permits the system to be easily scaled up or down in overall size and capacity. A user is able to select between traditional video program material, such as scheduled special events and on-demand feature

10 length films, as well as Internet access, video games and computer applications. Assignable Computing Devices (ACDs), one type of audiovisual serving device within the system, are used for a number of functions including providing Internet access to a user, controlling the menu-driven process of selecting program material and providing computer applications to users. Other types of audiovisual serving

15 devices, which are more specialized than the ACDs, provide program material such as scheduled special events, on-demand feature length films and video games. The user communicates with the ACDs through an intuitive graphical user interface (GUI) while selecting program material to view through a series of menus. These menus are easy to update and tailor to the preferences of an

20 individual user. Internet access is provided by assigning an ACD to the user. Computer inputs are provided by in-room devices connected to the terminus of the video distribution system. Computer outputs are converted to audiovisual signals

suitable for display by an in-room monitor such as a television set. In this way a user need not have an in-room computer to obtain internet access and a number of ACDs can provide for the computer needs of a larger number of user's through this dynamic assignment scheme.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a system block diagram showing a presently preferred

5 embodiment of the invention.

FIG. 2 is a flow diagram showing a process in accordance with a presently preferred embodiment of the invention.

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Those of ordinary skill in the art will realize that the following description of the present invention is illustrative only and not intended to be in any way
 5 limiting. Other embodiments of the invention will readily suggest themselves to such skilled persons after a perusal of the within disclosure.

The video distribution system for distributing video program material among users of a lodging or similar facility utilizes a host computing device that allocates tasks among a number of audiovisual serving devices. By allocating
 10 tasks to the audiovisual serving devices, the host is able to service a plurality of users and provide each user access to a pool of audiovisual serving devices.

Referring to FIG. 1, three major components are provide: the central host computer shown as the System Management Subsystem (SMS) 10 for managing the overall system, the programming subsystem 12, which preferably includes
 15 numerous audiovisual serving devices 8 which serve as sources of video program material, and the Room Communication Subsystem (RCS) 14 for delivering the program material to the user.

The system delivers to the users a variety of types of program material from a variety of sources. The types of program materials include, but are not limited
 20 to, access to the Internet, computers running application software, on-demand feature length and other films, scheduled special events, scheduled video programs, video games and the like. Program material may come from

videotapes, satellite and terrestrial broadcasts, the Internet, and material stored on video servers such as a magneto-optical jukebox-type digital video servers and the like. Those of ordinary skill in the art will recognize that the term video server encompasses many types of individual devices known in the art, both analog and digital, including, but not limited to, banks of video tape players, video jukeboxes, magnetic disk arrays storing digital representations of video signals, banks of digital video disk (DVD) players, computing devices capable of outputting audiovisual program material, and the like. The present invention uses a broad definition of audiovisual serving device to include all such devices capable of producing or delivering audiovisual program material to a user.

The SMS 10, or host, manages the overall video distribution system, which includes maintaining data on the system resources, and directing signals between the user and audiovisual serving devices through the RCS 14. The program material distributed to the users is all contained within the individual audiovisual serving devices 8. The SMS 10 directs a particular audiovisual serving device 8 to deliver program material to the user. By allocating the time-intensive tasks of presenting users with program material to the programming subsystem 12, the SMS 10 is able to service a relatively large number of users.

User inputs and interactions with the programming subsystem 12 are made through the Room Communications Subsystem (RCS) 14 at the direction of the SMS 10. That is, the RCS 14 facilitates routing of both the output from an audiovisual serving device to an individual user and user communications, if any,

back to the audiovisual serving device and/or the SMS 10 as appropriate. The output of the audiovisual serving device will be an audiovisual (AV) signal that the RCS 14 will direct to the user's monitor. The terms "monitor" and "user's monitor" in the context of this disclosure are intended to include a wide range of displays, such as a TV display in the user's room and similar devices such as video monitors and the like.

The SMS 10 functions as a host computer directing a number of audiovisual serving devices to present program material to the user, as well as managing the overall system operations. In accordance with a presently preferred embodiment of the present invention, the SMS 10 may include a single computing device operating under the control of an operating system such as WINDOWS NT™ available from Microsoft Corporation of Redmond, Washington. However, there is no requirement that any particular type of computing device or any particular operating system be used, as will be recognized by those of ordinary skill in the art. The SMS 10 manages the overall system and allocates tasks by communicating with the programming subsystem 12 using a standard data communications protocol such as TCP/IP socket connections. Those of ordinary skill in the art will recognize that many convenient communications protocols may be utilized, and the present invention is not intended to be limited to the use of TCP/IP socket connections for communications. Through these communications the SMS 10 keeps track of the current system resources and manages the overall system operations. At

initialization or power up, each audiovisual serving device opens a TCP/IP socket connection with the SMS 10. After establishing the connection, an initialization message is transmitted to the SMS 10, followed by a response from the SMS 10.

Next, the audiovisual serving devices each transmit data to the SMS 10 describing

5 their respective device hardware configurations, whether they are on-line or off-line and the RF communication channel that is assigned to the audiovisual serving device. Through this exchange of signals, the SMS 10 compiles a database of the audiovisual serving devices present in the system. Table 1 lists a set of system

10 commands used to compile this database in accordance with a presently preferred embodiment of the present invention, defining the variables to use and the format of such commands is within the knowledge of those of ordinary skill in the art.

Those of ordinary skill in the art will also recognize that many different sets of such commands may be utilized for such communications and the present invention is not intended to be limited to those listed in Table 1.

System Commands

<u>Name</u>	<u>Path - FIG. 1</u>	<u>Description</u>
INIT	24, 28 and 32	Inform SMS that subsystem has been initialized
RESP	22, 26 and 30	Response to INIT and synchronize the time
DISC	24, 28 and 32	Subsystem is going off-line
PING	22, 26 and 30	Verify communications with subsystem
SHUTDOWN	22, 26 and 30	Direct subsystem to shutdown
TSYN	22, 26 and 30	Re-synchronize time
MISC	22, 24, 26, 28, 30 and 32	General purpose test message
VER	22, 24, 26, 28, 30 and 32	Verify a command has been properly completed
ERR	24, 28 and 32	Inform SMS that an error has incurred in the subsystem

TABLE 1

To allow for continued system operations during occasional malfunctions of individual audiovisual serving devices, the SMS 10 sends a communication test message (a conventional “ping” message) after a defined period of time passes without any communications between an audiovisual serving device and the SMS 10. The audiovisual serving device responds by sending a verification message back to the SMS 10 indicating that it is functioning properly, or the SMS 10 is alerted to take action. In accordance with a presently preferred embodiment of the present invention the SMS 10 closes the socket connections of audiovisual serving devices that do not respond after a defined number of pings and updates the database of currently available system resources. An audiovisual serving device that loses its socket connection resets and periodically attempts to reestablish the socket connection. The audiovisual serving device is added to the database of

available system resources after a successful exchange of initialization and response messages between the audiovisual serving devices and the SMS 10. In this way, the SMS 10 not only accounts for audiovisual serving devices added or removed before startup but continuously monitors the system resources. Those of
5 ordinary skill in the art will recognize that the use of ping messages is one of many ways the SMS 10 may monitor and manage the system resources and that the present invention is not intended to be limited to this particular mode of operation.

The SMS 10 continuously keeps track of the currently available system resources. For example, when the SMS 10 directs an audiovisual serving device
10 to provide a videotape to a user, both that particular tape and the audiovisual serving device will no longer be available to other users for the duration of the videotape, plus the time needed to rewind. To track the availability of the audiovisual serving devices and their resources, the present invention uses
15 messages sent from the audiovisual serving device to the SMS 10 noting a change in the status when the audiovisual serving device has started or finished a task, such as playing a particular videotape. The SMS 10 uses this message to update the database of currently available system resources.

The SMS 10 allocates the tasks of providing program material to the users among the various audiovisual serving devices. In accordance with a presently
20 preferred embodiment of the present invention, this is a two step procedure. First, the user is guided through a menu-driven process of selecting and ordering from a list of currently available program material by an audiovisual serving device

which is also an Assignable Commuting Device (ACD (discussed in detail below).

Second, the program material is provided to the user directly by the audiovisual serving device. In both steps, allocating these tasks to audiovisual serving devices frees the SMS 10 to service other users.

5 In accordance with a presently preferred embodiment of the present invention, a list of currently available program material available is tracked using titles. The SMS 10 maintains the list. When the system is initialized, the SMS 10 queries the audiovisual serving devices for the available program material. The audiovisual serving devices each respond with a list of titles. These
10 communications are made using a standard data communications protocol such as TCP/IP socket connections. This list of currently available program materials is continuously updated. Information for updates can be compiled through change in status messages sent from the audiovisual serving devices to the SMS 10 or from the audiovisual serving devices to the SMS 10, indicating that a title is in use or is
15 currently available. The list can vary in concert with the available system resources, for example, if all the videotape players are in use presenting program material to other users, then all of the videotape program material would be unavailable to new users. Conversely, if an additional audiovisual serving device is added to the system with new program titles, the list of currently available titles
20 is preferably updated. Commands used to compile an initial list of program material and to keep track of changes, in accordance with a presently preferred embodiment of the present invention, are shown in Tables 2 and 3 respectively.

Defining the variables to use and the format of such commands is within the knowledge of those of ordinary skill in the art. Those of ordinary skill in the art will also recognize that many different sets of such commands may be utilized and the present invention is not intended to be limited to those in Tables 2 and 3. In

- 5 these tables, the abbreviation “PS” is used to designate the programming subsystem 12.

Title Resources Commands		
<u>Name</u>	<u>Path - FIG. 1</u>	<u>Description</u>
QTITLE	22, 26 and 30	SMS polls PS for available titles
Q1TITLE	22, 26 and 30	SMS polls PS for international title information
QHARD	22, 26 and 30	SMS polls PS for hardware information
QSTIL	22, 26 and 30	SMS polls PS for schedule information
QSTIM	30	SMS polls SPS for schedule information
QSYS	22, 26 and 30	SMS polls a device for current status
TINF	24, 28 and 32	Return title information
ITINF	24, 28 and 32	Return international title information
DINF	24, 28 and 32	Return device configuration information
MINE	24, 28 and 32	Return device modulator information
LINE	24, 28 and 32	Return device LonTalk information, for user communications
PINF	24, 28 and 32	Return RS232 port setup information
SINF	24, 28 and 32	Return schedule information for a title
SYINF	24, 28 and 32	Return device status information
CSTATE	22, 24, 26, 28, 30 and 32	Change in device status
TREQ	22, 26 and 30	SMS directs PS to present program material to a user
TCTRL	22, 26 and 30	SMS informs PS that user stopped or canceled the material

TABLE 2

Status Commands

<u>Name</u>	<u>Path - FIG. 1</u>	<u>Description</u>
TAVL	24,28 and 32	PS notifies SMS on availability of a title
TEND	24,28 and 32	PS notifies SMS a user has completed viewing
SSAVL	22, 24, 26, 28, 30 and 32	A PS is out of resources, broadcast to system
TRES	24,28 and 32	Acknowledge allocation of PS by SMS to present material
TPO	24,28 and 32	Free-preview time is over
CHARGE	22, 26 and 30	Poll PS on charge information for program material
CINF	24,28 and 32	Return charge information for program material
SCHEDULE	22, 26 and 30	SMS allocates PS to present program material at specified time

TABLE 3

The SMS 10 preferably maintains a database on the individual users. This data includes the program material that an individual user views or purchases, and is made available by the SMS 10 for a variety of purposes including billing. In accordance with a presently preferred embodiment of the present invention, user data including previous purchases, a preferred language, a choice of whether or not to block certain program materials such as adult program materials and a choice of whether or not to block pay-per-view program material is used to customize the menus presented to the user.

10 The programming subsystem 12 provides the selected program material for routing to the user. Referring to FIG. 1, the programming subsystem 12 may include numerous audiovisual serving devices which may be thought of as being divided into three subsystems based on the category of program material each provides. These include the Scheduled Programming Subsystem (SPS) 16 for
15 presenting scheduled program content such as special events, the Linear

Programming Subsystem (LPS) 18 for presenting on-demand program content such as feature length films and the Interactive Programming Subsystem (IPS) 20 for presenting interactive program content such as video game applications and menus. Within each of these subsystems (not all of which must be present in a given system) there may be one or more audiovisual serving devices that provide program material to the users, such as a group of digital video servers within the LPS 18, each one with the capacity to simultaneously provide multiple users with on-demand streams of program material.

The present invention preferably uses Assignable Computing Devices (ACDs) as programming subsystem 12 audiovisual serving devices in various applications. For example, in accordance with a presently preferred embodiment of the present invention IBM-compatible personal computers (PCs) are used as ACDs to generate the menus for the user to select program material. This selection is not intended to be limiting, however. In accordance with the present invention, an ACD may be any computing device capable of performing a task assigned to it. Such devices are intended to include, but be limited to, game computing devices such as the NINTENDO 64 (TM) a product of the Nintendo Corporation of Japan and the SONY PLAY STATION (TM) a product of the Sony Corporation of Japan, Apple-based personal computers available from Apple Computer Corp. of Cupertino, California, UNIX-based computers available from a number of vendors, single-purpose application devices such as computing chips

with pre-programmed application programs loaded from read-only memory (ROM), and the like.

The present invention treats presenting menus for the user to select program material as a special mode of presenting program material. This task is inherently interactive and is allocated to the IPS 20. The menu selection process includes presenting the user with a set of menus using a graphical user interface (GUI), and accepting user inputs that will interactively step the user through viewing the list of program material and allow the user to make a selection. The information for generating these menus, such as the currently available system resources, is maintained by the SMS 10 and used by or passed to the ACD audiovisual serving device. The menus may be written in Hypertext Markup Language (HTML) or any other convenient programming language. The use of HTML makes the individual menus particularly easy to update. The result of the menu selection process is a title, or other such identification, of the program material the user wishes to view.

Given the title of the program material, the SMS 10 allocates the task of presenting the program material to a particular audiovisual serving device within the programming subsystem 12, which will then operate with the RCS 14 to route the selected material to the user. During the period of time that the program material is being presented to the user and other times when the user is in communication with device other than the SMS 10, the SMS 10 is free to service other users. Those of ordinary skill in the art will notice that it is also possible to

use the same ACD that provided the menus to the user to handle the allocations of the task of presenting the program material to the user by causing an appropriate audiovisual serving device to present the selected program material rather than queuing the request through the SMS 10.

5 The three subsystems of the programming subsystem 12, the SPS 16, LPS 18 and IPS 20 differ in the type of programming material each contains, which defines the interaction each generally expects with the user. For each, the identity of the user and the program material are known from the menu selection process and these are passed as described above to an audiovisual serving device that has
10 been allocated to presenting the material to the user. This same information is used by the RCS 14 to facilitate routing graphical displays and communications between the user and the audiovisual serving device.

 The SPS 16 delivers real-time or scheduled program content. The content may include out-of-market sports events, special events and other scheduled
15 programs. This type of programming is often regionally or nationally distributed. The source of program material delivered by the SPS 16 may include terrestrial broadcast, local cable television and satellite-delivered programming such as DirecTV™, C-band satellite program feeds and the like. In accordance with a
 presently preferred embodiment of the present invention, the SPS 16 program
20 material does not include the traditional free-to-guest programming which may be provided to the guest free by not invoking the video distribution system.

Each SPS 16 audiovisual serving device, like the other audiovisual serving devices, sends data to the SMS 10 when the video distribution system is initialized or a new socket connection is established between the audiovisual serving device and the SMS 10. This data preferably includes a list of the available program

5 material titles, program material start and end times, the identification of the communications channel assigned to it and the current audiovisual serving device configuration. The list of available program material is used to generate menus for selection by users. The program material scheduled start and end times are also reflected in menus. The identification of the assigned communications channel is

10 used by the RCS 14 to route the AV signal to the user's monitor. The device configuration specifies that the particular device is a SPS 16 audiovisual serving device and its operating characteristics that differ from those of other "generic" SPS 16 audiovisual serving devices. For example, some SPS 16 audiovisual serving devices may be configured to deliver a fixed schedule of program material

15 to the user, without allowing the user to "switch channels." Others, such as those SPS 16 audiovisual serving devices that supply out-of-market sports events programming, may be configured to allow a user to switch among a number of sports events for a predetermined amount of time. For this later configuration, the user communicates with the SPS 16 audiovisual serving device, directing it to

20 switch among the sports events. This communication is conducted through the RCS 14.

In accordance with one embodiment of the present invention, the menu information for the SPS 16 program material includes dynamic titles. A channel of a satellite may be dedicated to updating the schedule of program material, such as including information that a sports event is delayed due to rain. This updated
5 schedule is then reflected in the menus presented to users.

The LPS 18 delivers linear program content. Typically, this subsystem works in a video-on-demand basis. The LPS 18 content is characterized by the deterministic, “start-to-finish” nature of its playback. Program content may take the form of feature length films, short programs, advertisements and other video
10 programming. In accordance with one embodiment of the present invention, the LPS 18 maintains data fields of start and end dates for the program material. When the current date is outside the range of those start and end dates the LPS 18 does not include the program material in the list of current titles data passed to the SMS 10. This feature is intended to add flexibility in supplying LPS 18 program
15 material to a facility, program material can be delivered and loaded on the audiovisual serving devices outside of the dates the facility is licensed to present it to users.

The LPS 18 operation begins when the SMS 10 directs that a specific title be presented to the user. The LPS 18 generally requires little or no
20 communication between the audiovisual serving device and the user once the delivery of program material begins. Those of ordinary skill in the art will recognize that storage and playback of program material on an audiovisual serving

device can take many forms and use many formats, such as MPEG-2 and the like, however the present invention is not intended to be limited to any particular data storage device or compression format.

In accordance with a presently preferred embodiment of the present

5 invention, the LPS 18 system is used to store and playback “broadcast channels” or initial menus that are presented to the user when the system is activated in the user’s room. The broadcast channels are preferably customized for each facility, to advertise the available features and any other information a facility wishes to convey to guests. In accordance with one embodiment of the present invention,
10 multiple broadcast channels are stored on the LPS 18, with the one presented to a particular guest determined by data such as a preferred language and/or whether or not the guest has requested the blocking of any program material, and if a guest is attending a conference at the facility. Those of ordinary skill in the art will recognize that presenting a broadcast channel to the user is not functionally
15 necessary, only that there must be a means for the user to turn the system on. Effectively, the initial menu is an “on” switch, which is preferably presented with advertising material in the form of a broadcast channel. For example, the system could come up and play the broadcast channel advertising available feature length films and instructing the user to press a “menu” button on the remote control in
20 order to select one for viewing. Those ordinary skill in the art will recognize that a number of different approaches could also be used.

The IPS 20 delivers interactive program content. This program interactive content preferably includes Internet access, video game applications, computer applications and a system of menus for a user to select program material. The IPS 20 operations are started with a message from the SMS 10 directing a particular
 5 title be presented to a user. The RCS 14 then relays communications between the audiovisual serving device and the user and delivers the AV signal to the user. The IPS 20 program material typically requires near-real-time two-way communication with the user.

In accordance with one embodiment of the present invention, two types of
 10 devices are used for the IPS 20 audiovisual serving devices. Game computers may be used for presenting video game applications and IBM-compatible personal computers (PC) may be used as ACDs for other interactive program material. Both devices use the user's monitor to display information. Preferably, each guest room is supplied with a gamepad 54 for use with the game computer and a
 15 keyboard 52 for use with the PC. In accordance with a presently preferred embodiment of the preferred invention, the IPS 20 video game audiovisual serving devices maintain data fields of start and end dates for the program material. When the current date is outside the range of those start and end dates the IPS 20 video game audiovisual serving devices do not include the program material in the list of
 20 currently titles data passed to the SMS 10.

Access to the Internet is another type of program material provided by the IPS 20 using ACDs. The ACD establishes a connection to the Internet, through

any number of conventional means such as by modem, direct internet connection, ISDN connection, satellite internet connection and x DSL connection, to name a few, and by routing signals through the RCS 14 allows the user to access the Internet with the ACD serving us the user's client machine. The monitor in the user's room presents a display, such as a web page the user has selected to view, and the user controls the display using the in-room communications control device. For example, text and directional commands may be entered through the keyboard. Internet access may therefore be provided to users without the need for any in-room computing device provided by the user or by the facility.

In accordance with a recently preferred embodiment of the present invention, when a user is provided access to the Internet, the system modifies web pages and the browser to enhance usability with NTSC-TV monitors. This is done because the typical monitor in a lodging facility lacks the display resolution most PC users expect. These modifications include: increasing the font size of web pages to a predetermined minimum, replacing white backgrounds with a level of gray to reduce contrast thus reducing flicker and enlarging boxes for displaying text (such as passwords and URLs) with enlarged font sizes. With higher resolution HDTV monitors, this additional processing may prove unnecessary. The browser application provided to the user may be configured to accept conventional "plug-in" applications as known to those of skill in the art.

The IPS 20 ACD audiovisual serving devices also provide program material that may include computer applications programs. A number of computer

applications such as word processors and spreadsheets would preferably reside on an ACD. The present invention may also include computer applications that in turn play material at the request of a user, such as applications to play compact disks (CDs) or the like. However, the present invention is not intended to be

5 limited to any particular type of computer application program. A user selection of an application would cause a title to be sent by the SMS 10, allocating an ACD to present the application to the user. Communications and the AV signals are relayed by the RCS 14 in a manner similar to other program material. In accordance with a preferred embodiment of the present invention, the computer

10 applications and capabilities available for use by the user would be carefully selected to prevent unauthorized access into system files.

The RCS 14 is the third major component of the video distribution system, it facilitates the delivery of the program material from a particular audiovisual serving device in the programming system 12 to the user. Program material

15 coming from the programming subsystem 12 is in the form of streams of audiovisual (AV) data typically including an audio component and a video component, although both are not required and more than one instance of an audio component and/or a video component may be present. Each of these streams of AV data is the output of a single audiovisual serving device, and is preferably

20 connected to a unique RF modulator assigned to that audiovisual serving device and providing a television output signal on a selected RF frequency. Typically, the frequencies used are in the UHF portion of the television band, but any

convenient frequency may be used including new HDTV allocated frequencies.

This direct connection of an RF modulator to each audiovisual serving device removes the need for a crosspoint switch. The audiovisual serving device outputs are a set of AV signals each modulated to a selected TV channel of a particular RF

5 frequency, combined and distributed to the monitors of the users over the RCS 14.

Note that while this is an advantage of the present invention, there is no requirement that each audiovisual serving device be provided with an independent RF modulator for each output channel and a cross-point switch could still be used to connect a plurality of audiovisual serving devices with RF modulators.

10 The RCS 14 routes the modulated program material to the user and acts as a conduit for all direct communications with the user. The SMS 10 directs the RCS 14 where to route the signal. Typically, there will be numerous users using the system at a given time. The RCS 14 relays the communications between the various users and the various audiovisual serving devices in the programming

15 subsystem 12, and relays the AV signals to the user's monitor, under the direction of the SMS 10. The program material is preferably modulated to a particular frequency range by RF modulators associated with the audiovisual serving device that provides the material, and distributed through a trunk distribution system to all rooms connected to the system. The RCS 14 tunes the user's monitor to the

20 correct "channel" to view the program material from the correct audiovisual serving device. The RCS 14 preferably includes a remote control device 50, keyboard device 52 and gamepad 54 in the user's room. Communication signals

between these devices and the audiovisual serving device are necessary in many contexts. In parallel with relaying the AV signal to the user's monitor, the RCS 14 relays the communication signals between these devices and the programming subsystem 12 in a conventional manner such as by modulating a signal onto a carrier inserted onto the coaxial (or other) distribution line coming into the user's room. The modulation technique can be any convenient scheme such as frequency shift keying (FSK), phase shift keying (PSK), frequency modulation (FM), packet, and the like. The distribution line can be a coaxial cable, a wireless distribution link, or other distribution link as would be known to those of ordinary skill in the art.

Referring to FIG. 2, a flow chart of the process 100 in accordance with a presently preferred embodiment of the present invention is shown. The presentation of a broadcast channel on the user's monitor 102 precedes the user indicating a desire to access the system 104. The SMS 10 allocates a programming subsystem 12 audiovisual serving device ACD to present the user with a set of menus 106 and removes that audiovisual serving device from a list of available audiovisual serving devices 120. The audiovisual serving device then presents the menus to the user 108, for the user to select program material 110 and passes the title of the program material to the SMS 10. The audiovisual serving device that provided the menu is then available for other tasks, and this is reflected in the updating of the list of available audiovisual serving devices 120. Based on the program material selected, the SMS 10 allocates an audiovisual serving

devices to present the material to the user 112, and again updates the list of available audiovisual serving device 120. The audiovisual serving device presents the program material to the user 114 and creates a record of doing so 116. When the user has completed viewing the program material 118, the audiovisual serving

5 device providing the material is made available for other tasks and this information is reflected in the list of available audiovisual serving devices. In each instance of updating the list of available audiovisual serving devices, a list of available program material is contemporaneously updated.

While embodiments and applications of this invention have been shown

10 and described, it would be apparent to those skilled in the art, after a perusal of this disclosure, that many more modifications than mentioned above are possible without departing from the inventive concepts herein. The invention, therefore, is not to be restricted except in the spirit of the appended claims.

CLAIMS

What is claimed is:

1. A method for providing data communications network access to a user,

5 comprising:

providing the user with an audiovisual display monitor;

providing the other with at least one input device;

allocating an assignable computing device (ACD) to the user in response to
the user's request for data communications network access;

10 creating a connection between the ACD on the data communications
network;

preparing an audiovisual display based on signals received from the data
communications network with the ACD;

displaying the audiovisual display on the audiovisual display monitor;

15 receiving signals from the at least one input device at the ACD;

converting said received signals to signals compatible with the data
communications network; and

sending said compatible signals to the data communications network.

2. A method in accordance with claim 1 wherein displaying includes:

20 converting said audiovisual display to a video signal;

modulating said video signal onto an RF carrier having a specific channel
assignment;

transmitting said RF carrier to the audiovisual display monitor; and
 tuning the audiovisual display monitor to said specific channel so is to
 demodulate the RF carrier, receive the video signal and display the audiovisual
 display.

- 5 3. A method for presenting program material from a plurality of program
 sources to users using a host computing device and allocating tasks among a
 plurality of audiovisual serving devices, said method comprising:

responding to a user request to order program material by selecting one of a
 plurality of Assignable Computing Devices (ACDs) to generate a menu, said menu
 10 listing available program material;

presenting the user with said menu over a Room Communication
 Subsystem (RCS);

receiving a program selection from the user over a Room Communication
 Subsystem (RCS);

15 responding to said selection of program material by selecting one of a
 plurality of audiovisual serving devices to present the program material; and
 presenting the program material to the user over the RCS.

4. A method in accordance with claim 3 wherein said ACD is assigned to
 respond to the user request by the host computing device in communication with
 20 the user.

5. A method in accordance with claim 3 wherein said audiovisual serving
 device is assigned to respond to the user selection by the host computing.

6. A method in accordance with claim 3 wherein said audiovisual serving device is assigned to respond to the user request by the ACD in communication with the user.
7. A method in accordance with claim 3 further comprising creating a list of
5 available ACDs before selecting said ACD to generate said menu.
8. A method in accordance with claim 3 further comprising creating a list of available audiovisual serving devices before selecting said audiovisual serving device to present the program material.
9. A method in accordance with claim 3 wherein said menu is updated in
10 response to selecting said ACD to generate said menu.
10. A method in accordance with claim 3 wherein said menu is updated in response to receiving said program selection from the user.
11. A method in accordance with claim 3 further comprising creating a set of user data, said set of user data listing stated user preferences.
12. A method in accordance with claim 11 wherein said menu is modified to
15 reflect said set of user data.
13. A method in accordance with claim 3 further comprising presenting the user with a broadcast channel.
14. A method in accordance with claim 13 further comprising creating a set of
20 user data, said set of user data listing stated user preferences.
15. A method in accordance with claim 14 wherein said broadcast channel is modified to reflect said set of user preferences.

16. A method in accordance with claim 3 wherein adding an additional audiovisual serving device causes a socket connection to be made to the host.

17. A method in accordance with claim 3 wherein adding an additional audiovisual serving device causes an exchange of signals between the host and

5 said additional audiovisual serving device.

18. A method in accordance with claim 3 further comprising polling the audiovisual serving device for status after a first defined interval of time.

19. A method in accordance with claim 18 wherein the audiovisual serving device is restarted in response to instructions from the host after a second defined
10 interval of time.

20. An apparatus for presenting program material from a plurality of program sources to users using a host computing device and a plurality of audiovisual serving devices, comprising:

a programming subsystem;

15 a Room Communication Subsystem (RCS);

a Site Management Subsystem (SMS);

said RCS connecting a plurality of user terminals to the system;

said programming subsystem including a plurality of audiovisual serving devices communicating with the user terminals over said RCS; and

20 said SMS assigning an Assignable Computing Device (ACD) audiovisual serving device to communicate with a user terminal in response to an initial communication from a user terminal.

21. An apparatus in accordance with claim 20 wherein said SMS is adapted to keep track of the availability of said audiovisual serving devices when assigning allocating tasks.

22. An apparatus in accordance with claim 20 wherein said SMS is adapted to
5 keep track of the availability of said ACD devices when assigning allocating tasks.

23. An apparatus in accordance with claim 20 wherein said programming subsystem communicates an update of the availability of the audiovisual serving devices to said SMS.

24. An apparatus in accordance with claim 20 wherein said SMS polls said
10 programming subsystem for an update of the availability of audiovisual serving devices.

25. An apparatus in accordance with claim 20 also comprising a menu responsive to a list of currently available program material.

26. An apparatus in accordance with claim 25 further comprising a set of user
15 data, said user data listing stated user preferences.

27. An apparatus in accordance with claim 26 wherein said menu is responsive to said set of user data.

28. An apparatus in accordance with claim 20 further comprising a broadcast channel.

20 29. An apparatus in accordance with claim 28 further comprising a set of user data, said user data listing stated user preferences.

30. An apparatus in accordance with claim 29 wherein said broadcast channel is responsive to said set of user data.

31. An apparatus in accordance with claim 20 wherein said programming subsystem includes an Interactive Programming System (IPS) for presenting

5 interactive program material.

32. An apparatus in accordance with claim 31 wherein said interactive program material includes video game applications.

33. An apparatus in accordance with claim 31 wherein said interactive program material includes computer applications.

10 34. An apparatus in accordance with claim 31 wherein said interactive program material includes access to the Internet.

35. An apparatus in accordance with claim 31 wherein said interactive program material includes access to the Internet with graphic displays modified for viewing on a TV monitor.

ABSTRACT OF THE DISCLOSURE

A method and system for video distribution among a plurality of users uses
5 a host computing device that allocates tasks among a number of audiovisual
serving devices. The system architecture permits a single host to handle a
plurality of simultaneous users and permits the system to be easily scaled up or
down in overall size and capacity. A user is able to select between traditional
video program material, such as scheduled special events and on-demand feature
10 length films, as well as Internet access, video games and computer applications.
Assignable Computing Devices (ACDs), one type of audiovisual serving device
within the system, are used for a number of functions including providing Internet
access to a user, controlling the menu-driven process of selecting program material
and providing computer applications to users. Other types of audiovisual serving
15 devices, which are more specialized than the ACDs, provide program material
such as scheduled special events, on-demand feature length films and video
games. The user communicates with the ACDs through an intuitive graphical user
interface (GUI) while selecting program material to view through a series of
menus. These menus are easy to update and tailor to the preferences of an
20 individual user. Internet access is provided by assigning an ACD to the user.
Computer inputs are provided by in-room devices connected to the terminus of the
video distribution system. Computer outputs are converted to audiovisual signals

suitable for display by an in-room monitor such as a television set. In this way a user need not have an in-room computer to obtain internet access and a number of ACDs can provide for the computer needs of a larger number of user's through this dynamic assignment scheme.

ONCO-002





Fig. 1

EL048467211US

100

Fig. 2